



MT 40 SRD T (XP)

TECHNICAL DATA

MT2T0681051603803GP

Type	3/8" tufted sand dressed synthetic grass carpet, straight stitch pattern	
Pile content	100% polyethylene monofilament, 6.000/3 dTex, 280/140 microns combined with 100% Thiolon XP fibrillated yarn, U.V.-resistant, 5.500/1 dTex, curled	
Primary backing	Double 100% PP Thiobac, black, U.V.- stabilized, weight ca. 265 gr/m ²	
Secondary backing	Latex compound with a base of styrene- butadiene (SBR), with drainage holes	
Pile height	± 38 mm	+/- 10%
Total thickness	± 40 mm	+/- 10%
Stitch rate per 10 cm (width)	± 10,5	
Stitch rate per 10 cm (length)	± 16	+/- 1
Number of tufts/m ²	± 16.800	+/- 5%
Face weight	± 1.645 gr/m ²	+/- 10%
Weight primary backing	± 265 gr/m ²	+/- 10%
Weight secondary backing	± 1.000 gr/m ²	+/- 10%
Total weight	± 2.910 gr/m ²	+/- 10%
Roll width	410 cm	+/- 2 cm
Roll length	as required	
Tuft bind	≥ 30 Newton	
Water permeability	± 60 ltr/m ² /min (unfilled)	
Colour fastness	Xenon test : blue-scale>7, grey-scale>4	

COLOUR

Olive green. White and yellow for line marking.

INSTALLATION METHOD

Loose laid on bound or unbound sub base, with or without a shock pad, glued seams.

INFILL (RECOMMENDED)

1st layer : 10 mm of sand (80% round), size of granules 0.3-0.8 mm, app. 14 kg/m²
 2nd layer : 10 mm of rubber 0.8-2.5 mm, app. 5,5 kg/m²

PRODUCT APPLICATION

Multifunctional